



Gunnebo ModuleGuard-SR T2

The T2 certified lightweight modular strong rooms to secure customer valuables against burglary

ModuleGuard-SR T2 is the new generation of modular strong room. Available in grades I, III and IV, the solution can be tailored for existing structure of buildings, even where dimensions are restricted.

Easy Installation

Lightweight panels allow for placements where floor loads are limited. As an alternative to the welded assembling, certified bolts assembling solution is offered and enables quick implementation in required environments.

Industry proved

Fire rating and Certified with T2 and certified by ECB•S according to EN 1143-1 standard. But also provides resistance from basic tools such as drills, sledgehammers, and sophisticated thermal and electrical equipment.

Customisation

Flexible and modular to meet required dimensions and needs. The constructions also empower assembly, disassembly, and expansion of a room.

More sustainable

No use of dangerous or toxic components for high performance. This solution prioritises environmental responsibility without compromising safety.

Possible application are reinforced protection for Retail, cash counting rooms, archives, storerooms (for weapons, pharmaceuticals), ATMs, etc.

Gunnebo ModuleGuard-SR T2

Product Specifications


Panels

Grade	Weight (kg/m ²) Burglary resistance	Weight (kg/m ²) Burglary & fire resistance	Weight (kg/m ²) Burglary resistance Bolted version	Thickness (mm)	Fire resistance (min)
I	60	63	65	75	60
III	136	139	141	75	90
IV	175	178	180	75	90

Max Internal Wall span: 4000 mm. Max Internal Roof span: 4000 mm.

Minimum room measurements

To be certified, the room must be six-sided and meet the minimum dimension requirements below.



Height (External/Internal): 2220/2070mm
Width (External/Internal): 2300/2150mm
Depth (External/Internal): 1650/1500mm

The specifications given are the minimum size for a certified ModuleGuard enclosure. They are based on a Grade III enclosure and a door with a clear opening width of 900mm. Larger sizes can be made to order. Please note, for extra large dimensions, an additional frame structure may be required for support.

T2 Burglary testing

ModuleGuard has been approved by ECB•S in accordance with the European EN 1143-1 standard for burglary protection in Grades I, III and IV. A range of attack tools were used to test ModuleGuard's level of resistance, from basic tools, such as drills and sledgehammers, to more sophisticated thermal and electrical equipment, such as an oxyacetylene torch.

Finish

The panel finish for ModuleGuard-SR T2 grade I is a steel surface. For grades III and IV, the exterior is a cement surface, while the interior is a steel surface.



Take advantage of our knowledge:
blog.gunnebo.com or www.gunnebo.com

GUNNEBO[®]
Safe Storage