Gunnebo Centurion-RD

Certified burglary-resistant vault door

- Grades X–XII certified by ECB•S for burglary resistance, in accordance with the EN 1143-1 certification
- The Centurion-RD has undergone additional testing to resist attack from diamond core-drill bits
- Door prepared for vault wall installation
- All Grades provide resistance against powerful diamond-core drill bits (certified by CD classification)

GUNNEBO®
Safe Storage

Gunnebo Centurion-RD

Product Specifications

Model	Overall thick-ness (mm)	External Height (mm)	Internal Height (mm)	External Width (mm)	Weight (kg)	Number of bolts
Grade X-XII	496	2486	2100	3000	9000	24

Dimensions can be increased up to 2845 mm for external height and to 2500 for internal height.

Testing

Centurion vault doors have been tested and certified in accordance with EN 1143-1, the European standard for burglary protection. This standard covers attacks from a variety of tools, including crowbars, high-powered disc cutters and oxyacetylene torches. The Round door has undergone additional testing to resist attack from diamond core-drill bits

Dimensions can be increased up to 2845 mm for external height and to 2500 for internal height.

Options

- Door hinge positions (left or right) can be specified
- Grill gate for added security of the main door
- Electric door opener for grill gate
- Door stopper
- Painting finishing (door and frame painted in RAL lightgrey 7035, Crane painted in RAL Black 7016 as a standard), other surface finishing upon request
- Handle black anodized

Key lock

- Kaba Mauer Primus 70011 (Class C)

Combination lock

- Kaba Mas LCC LG 1947 (Class C)

Electronic locks

- Gunnebo Encry™ (Class C, D)
- Kaba Paxos (Class C, D)

Design and production: Gunnebo. Photos Credits: Gunnebo. The data given in this material may be subject to change without further notice. The Gunnebo logos and "Gunnebo – For a safer world" are registered trademarks of Gunnebo AB.